

# Atlas Copco Portable Air compressors



## XAS 750 JD7 T3

This generation of the XAS 750 is more environment friendly, more fuel efficient and neatly packaged for serviceability.

Packaged in the new Size II low pressure (single axle, sound suppressed) enclosure, the XAS 750 JD7 is smaller and lighter than competitive packages, and has more key features and benefits. Confirming our commitment to performance, reliability and efficiency.



*Sustainable Productivity*

*Atlas Copco*



**Designed to your individual needs**

The XAS 750 JD7 is designed with innovative features to make your job easier. For example, all replacement parts are within easy reach so routine maintenance takes less time.

Atlas Copco listened to the sales force, and more importantly we listened to you. We understood your requirements and designed a reliable, high performance air compressor with a long lifetime, low operating costs, and high resale value.

- Guaranteed 750 CFM
- Roadlights standard
- Electronic control module
- Performance and diagnostics at your fingertips



Danger: Compressed air should never be supplied as breathing air unless air is properly purified for breathing. Atlas Copco assumes no responsibility or liability related to the purchaser's/user's breathing air system.

The information contained herein is general in nature and is not intended for specific construction, installation or application purposes

Technical		XAS 750 JD7 T3	
	Imperial		Metric
Normal effective working pressure	100 psi		7 bar
Maximum unloading working pressure	125 psi		8.6 bar
Actual free air delivery	750 cfm		345 l/s
Cooling system		Air / Oil	
Oil capacity	33 quarts		31.2 l
Engine John Deere			
Model number		6068HF285	
Cooling system		Liquid	
Number of cylinders		6	
Capacity of oil sump	36 quarts		34 l
Capacity of fuel tank	70 gal		265 l
Speed - maximum loaded		2000	
Speed - unloaded		1300	
Horsepower		200	
Unit dimensions			
Trailer mounted (LxWxH)	192 x 79 x 83 in		4877 x 2007 x 2108 mm
Support mounted (LxWxH)	132 x 67 x 83 in		3353 x 1702 x 2108 mm
Weight			
Trailer mounted - Wet	7760 lbs		3520 kg
Support mounted - Wet	6790 lbs		3080 kg

